





DIN 985 (ISO 10511)

Tuerca Autoblocante Baja Inserto Nylon



VENTA UNITARIA - CONSULTE PRECIOS SEGÚN CANTIDADES

d	M2,5	M3	M4	M5	M6	M8	M10	M12	M14
Paso	0,45	0,50	0,70	0,80	1,00	1,25	1,50	1,75	2,00
Paso Fino	-	-	-	-	-	1,00	1,00	1,50	-
m	3,5	2,4	2,9	3,2	4,0	5,5	6,5	8,0	9,5
h	2,3	2,4	2,9	3,2	6,0	8,0	10,0	12,0	14,0
s	5	5,5	7	8		13	17	19	22
e	5,50	6,01	7,66	8,79	11,05	14,38	18,90	21,10	24,49
Llave	5	5,5	7	8	10	13	17	19	22
Grado	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4

d	M16	M18	M20	M22	M24	M27	M30	M33	M36
Paso	2,00	2,50	2,50	2,50	3,00	3,00	3,50	3,50	4,00
Paso Fino	1,50	-	1,50	-	-	-	-	-	-
m	10,5	13,0	14,0	15,0	15,0	17,0	19,0	22,0	25,0
h	16,0	18,5	20,0	22,0	24,0	27,0	30,0	33,0	36,0
s	24	27	30	32	36	41	46	50	55
e	26,75	29,56	32,95	35,03	39,55	45,20	50,85	55,37	60,79
Llave	24	27	30	32	36	41	46	50	55
Grado	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4	A2 / A4

Disponibles en calidades **A2 (AISI-304)** / **A4 (AISI-316)**

Otras calidades disponibles bajo pedido (Duplex, Superduplex, Titanio, Inconel, Hastelloy, Nimonic, Monel).

Ejemplo de pedido: 985-M16A2 / Todas las medidas en mm / Otras dimensiones bajo pedido